Listing of Claims:

1. (Currently Amended) An apparatus for generating images of a subject on the basis of 3D-constructions from 3D-XRAY or 3D-Computer Tomography measurements, which subject comprises both natural tissue and one or more high-density objects, said apparatus comprising a measuring facility for executing said measurements, a distinguishing facility for distinguishing said one or more high-density objects and executing a separating procedure thereon for generating an image of regions of said natural tissue.

said apparatus being comprising:

a ramp-filtering facility for applying a ramp filter in the direction of rotation to such various projection measurements and a back-projecting facility fed by said ramp-filtering facility for back-projecting the various so filtered projections into a 3D-volume reconstruction;

a segmenting facility fed by said back-projecting facility for in said 3D-volume reconstruction segmenting said one or more high-density objects by a thresholding procedure and a forward projecting facility fed by said segmenting facility for executing a forward projection of the shadow(s) of the segmented one or more high-density objects onto the ramp-filtered projection, whilst marking the borders of said one or more high density objects in the ramp-filtered back-projections;

a suppressing facility fed by said forward projecting facility for suppressing said reconstructed one or more high-density objects from the original projection measurements and said suppressing facility is operative for executing an appropriate substitution of gray values derived from a physical neighbourhood of said one or more high-density objects in question;

and a retro-coupling facility fed by said suppressing facility for executing a back-projection of the various filtered projections with corrected profiles through exclusion of said suppressed one or more high-density objects and outputting a reconstruction result.

- 2. (Previously Presented) An apparatus as claimed in Claim 1, and furthermore comprising a superimposing facility fed by said forward projecting facility for receiving said one or more high-density objects for superimposing thereof onto said reconstruction result.
- 3. (Previously Presented) An apparatus as claimed in Claim 1, and comprising adapting means for relatively adapting the gray values of said one or more high-density objects and said natural tissue in a predetermined gray value range to show both of them at the same time.
- 4. (Previously Presented) A method of generating images of a human or animal body on the basis of 3D-constructions from 3D-XRAY or 3D-Computer Tomography measurements, which bodies comprise both natural tissue and one or more high-density objects, said method comprising the steps of executing said measurements, distinguishing said one or more high-density objects and executing a separating procedure thereon for generating an improved image of regions of said natural tissue,

said method being characterized by comprising the steps of:

applying a ramp filter in the direction of rotation to such various projection measurements and back-projecting the various filtered projections into a 3D-volume reconstruction;

in said 3D-volume reconstruction segmenting said one or more highdensity objects by a thresholding procedure and executing a forward projection of the shadow(s) of the segmented one or more high-density objects onto the ramp-filtered projection, thus marking the borders of said one or more high density objects in the rampfiltered back-projections;

suppressing said reconstructed one or more high-density objects from the original projection measurements whilst executing an appropriate substitution of gray values derived from a physical neighbourhood of said one or more high-density objects instead of said one or more high-density objects in question;

and secondarily executing a back-projection of the various filtered projections with corrected profiles and thereby without said suppressed one or more high-density objects.

5. (Previously Presented) A computer readable medium containing instructions for controlling a computer system to perform the steps of a method of generating images of a subject on the basis of 3D-constructions from 3D-XRAY or 3D-Computer Tomography measurements, which subject comprises both natural tissue and one or more high-density objects, said method comprising the steps of executing said measurements, distinguishing said one or more high-density objects and executing a separating procedure thereon for generating an improved image of regions of said natural tissue,

said method comprising the steps of:

applying a ramp filter in the direction of rotation to such various projection measurements and back-projecting the various filtered projections into a 3D-volume reconstruction,

in said 3D-volume reconstruction segmenting said one or more highdensity objects by a thresholding procedure and executing a forward projection of the shadow(s) of the segmented one ore more high-density objects onto the ramp-filtered projection, thus marking the borders of said one or more high density objects in the rampfiltered back-projections;

suppressing said reconstructed one or more high-density objects from the original projection measurements whilst executing an appropriate substitution of gray values derived from a physical neighbourhood of said one or more high-density objects instead of said one or more high-density objects in question;

and secondarily executing a back-projection of the various filtered projections with corrected profiles and thereby without said suppressed one or more high density objects.

6. (Canceled)